

Complete On-site Light Solution



**People.
Passion.
Performance.**



The CPLT V15 LED Light Tower



HIGH CRI SCORE
(COLOR RENDERING INDEX)
> 85
OUT OF 100
CLOSE TO NATURAL LIGHT

SPECIALLY DESIGNED DIRECTIONAL OPTICS
INCREDIBLE LIGHT DISTRIBUTION
NO LIGHT IS WASTED

Why LED light towers are the preferred choice?

When a larger space needs to be illuminated or an area requires illumination for a longer period of time it's advised to consider LED technology.

The CPLT V15 LED light tower ensure the right light based on the site and space that needs to be illuminated. These LED light towers only require approximately 1,400 W of power to illuminate an area of up to 5,000 m², while a metal halide light tower requires approximately 4,000 W. to light up 4,000 m².

Features:

- Robust: The CPLT V15 LED light tower has LED lamps which offer extra durability as compared to metal halide
- The expected lifetime of the LED lamp is more than 30,000 working hours.
- Ideal for extreme environments or heavy duty use, for example in construction or mining, as it provides enhanced coverage,
- Reduced fuel consumption and extended running hours.

	CPLT V15 LED
Fuel efficiency	0.9 l/h
Area coverage	5000 m ²
Mast	Vertical mast
Lamps durability	30,000 hrs
Transport efficiency	16 units in a truck
Enclosure	Red Rock canopy
Certification	CPCB II for complete unit

LIGHT TOWER

CPLT V15 LED

Performance data

Rated frequency	Hz	50
Rated voltage	V	230
Rated power (PRP)	kW	5
MX Sound Power level (LWA)	dB(A)	75

Engine

Model		Kohler KD441-GS12
Speed	rpm	3000
Rated net output (PRP)	kW	6.1

Alternator

Model		Sincro EP2CSL
Rated output	kVA	5
Insulation / Enclosure protection	IP	23

Consumption

Fuel tank capacity	l	80
Runtime with lamps ON	h	88

Lights

Floodlights		LED
Wattage	W	4 x 350

Mast

Type		Manual vertical, 5 section
Rotation	degrees	360
Maximum height	m	7.5

Dimensions inc. Transport fix towbar and weight

Length	mm	1700
Width	mm	1100
Height	mm	2500
Weight	kg	700

Chicago Pneumatic Products are robust, reliable, flexible, easy to maintain, versatile and can be tuned for all type of work.



M/s ROSA INTERNATIONAL

Company Add. : G-21, Ground Floor, NDM-2, Netaji Subhash Place
Pitampura, New Delhi-110 034

E-mail : rosa.international19@gmail.com
Phone : +91 9718-882-811