



Raising benchmarks of after sales support



**POWERFUL
FASTER
RELIABLE**

**FYN TECHNOLOGIES
PRIVATE LIMITED**

FYN

Raising benchmarks of aftersales support

fi Hydraulic Breaker Specification

No.	Items	Model	Fi 03	Fi 04	Fi 05 Open Type	Fi 06	Fi 12	Fi 20
1	Body Weight	KG	126	150	295	375	861	1760
2	Length (mm)	Top	1000	1140	1373	1699	2251	2823
3	Width (mm)	Top	176	177	350	353	438	620
4	Operating pressure	kg/cm ²	90-120	90-120	110-140	120-150	150-170	160-180
5	Oil Flow	l/min	20-40	20 - 50	40-70	50-90	80-110	140 above
6	Impact frequency	bpm	700-1200	600 - 1100	500-900	400-800	350-700	350-500
7	Dia. of Tool (Moi/Chisel/Blunt)	mm	45	53	68	75	100	140
8	Length of Tool	mm	500	580	700	710	1055	1300
9	Weight of Tool	kg	8	9	18	22	57	136
10	Suitable Carrier bucket Volume	m3	0.03-0.01	0.06 - 0.2	0.15-0.3	0.2-0.35	0.4-0.6	0.7-0.9
11	Suitable Carrier Weight	ton	1.2-3.5	2.5 - 4.5	4.0-7.0	6.0-9.0	10.0-16.0	18-26
12	Valve Type		Inward	Inward	Inward	Inward	Inward	Inward
13	Accumulator exists		No	No	No	No	No	Yes

SOLID TOOL
FOR
POWERFUL
RESULTS

